



SERIE IRR MULTI-ESTAGIO

MODELO	MANCAL	RPM	CV	DIMENSÕES EM MILÍMETROS (VAL. APROX.)								PESO APROX. Kg.
				A	B	C	D	L	E	H	J	
IRR-50-40-260/2	4A	1750	4	242	349	698	280	1014	310	446	225	123
			5	242	349	698	280	1014	310	446	225	126
			7,5	270	349	686	308	1035	310	446	225	138
IRR-50-40-260/3			7,5	270	349	686	308	1125	310	446	225	158
			10	398	362	725	336	1224	310	446	225	174
			IRR-65-50-260/2-X	5	242	349	698	280	1014	335	402	225
7,5				270	349	686	308	1035	335	402	225	138
7,5				270	349	686	308	1035	335	402	225	148
IRR-65-50-260/2			10	298	361	725	336	1134	335	402	225	164
			12,5	298	361	763	336	1134	335	402	225	190
			12,5	298	361	763	336	1224	343	402	225	210
IRR-65-50-260/3			15	298	361	763	336	1224	343	402	225	225
	20	298	431	863	336	1330	343	402	225	240		
	10	298	362	725	336	1134	343	402	225	152		
IRR-80-65-260/2	12,5	298	361	763	336	1134	343	402	225	170		
	15	298	361	763	336	1134	343	402	225	178		
	15	298	361	763	336	1224	343	402	225	190		
IRR-80-65-260/3	20	298	431	863	336	1330	343	402	225	195		
	25	350	500	1001	400	1453	440	395	300	310		
	30	350	519	1039	400	1478	440	395	300	353		
IRR-100-80-330/2	40	450	519	1039	500	1537	440	445	350	411		
	40	450	519	1039	500	1627	440	445	350	429		
	50	450	538	1077	500	1665	440	445	350	489		
IRR-100-80-330/3	60	486	589	1179	536	1750	440	445	350	573		
	75	470	652	1305	520	1820	670	787	380	653		
	100	470	681	1362	520	1820	670	787	380	715		
IRR-125-100-404/2	125	470	719	1439	520	1820	670	787	380	913		
	150	470	719	1439	520	1940	670	787	380	1062		
	175	470	766	1533	520	1940	670	787	380	1178		
IRR-125-100-404/3	200	470	766	1533	520	1940	670	787	380	1295		
	100						565					
	125						565					
IRR-150-125-360/2	7A						565					
							565					